

Foster Ranges

Foster Milano Range 6b - 48" x 27" - 7166 900

HIGHLIGHTS



Practicality

The bigger Foster Ranges are equipped with useful drawers that can be used to store kitchen stuffs.



Metal Knobs.

Exclusive and original the Foster metal knobs are an example of the strength and quality of the materials used. A distinctive feature shared by all the Foster elements in this collection, to form an elegant uniformity in the kitchen.



Telescopic guide

The practicality and accessibility to the cooking chamber are increased with the exclusive supply of full extension telescopic chromed racks.



Meat Probe

Experience the precision of professional cooking with our meat probe that measure in real time, the core temperature of your food.



RANGETOP SPECIFICATONS

Model	Milano Rangetop 6F - 48" x 27"
Dimensions	47 7/8" x 25 38/64"
Maintop	AISI 304 Stainless Steel
Finish	Satin Finish
Grids	Enamelled cast iron
Hob controls	Knobs
Knobs	solid Metal
Safety	Safety valves
Total power	64,950 Btu/h
Burners	6
Dual	900-15,500 Btu/h
rapid	2,300-10,750 Btu/h
semirapid	1,300-9,100 Btu/h
auxiliary	900-5,000 Btu/h
Simmer ring	3
Simmer Rate	900 Btu/h
Technical requirements	
Electrical supply	120V 60Hz
Gas std setting	Natural Gas
LP Gas conversion	kit for all burners included
Optional accessories	(2x) Cast iron wok support
Certifications	CSA certified for US & Canada

COOKING FUNCTIONS

 **Dual ventilation**

 **Delicate cooking**

 **Convection broil**

 **Defrost**

 **Pizza (lower convection)**

 **Keep warm (warm plus)**

 **Convection roast**

 **Proof warm**

 **Bake**

 **Lights**

 **Broil**

 **Fast preheating**

Foster Ranges

Foster Milano Range 6b - 48" x 27" - 7166 900

OVEN SPECIFICATONS

Model	Milano 30" single SS
Oven Type	Multifunction Pyrolytic Oven
Door finishing	Satin finish Stainless Steel
cooking Functions	13
Control Type	Electronic
Temperature control	Electronic
Commands	2 knobs / 6 touch keys
Language	English
Special features	
Cleaning function	Pyrolytic self clean
Probe T control	yes
Preset/last used temperature memory	yes
Preheat bar (25%, 50%, 75%, 100%)	yes
Automatic fast preheat	yes
Sabbath mode	Yes
Safety	Keyboard lock, Child door lock
Temperature unit	°C/°F
Clock format	12/24 Hours
Cooking Functions	
	Pyrolytic Sel Clean with automatic door lock; Dual convection Bake; convection Broil; Convection Roast; Lower Convection (Pizza function); Bake; Broil; Delicate cooking; Defrost; Proof warm; Keep warm (warm plus); Light; Fast preheating.
Cavity	
Usable capacity	4,1CuFt
cavity finish	Dark gray pyrolytic enamel
Rack positions	6
Lighting	Triple asimmetrical halogen (20W) lighting
Broil upper heating element	3500 W (240 V)
Upper aux element	1032 W (240 V)
Concealed bake lower heating element	3000 W (240 V)
Convection element	2 x 1300 W (240 V)
Door	
door Glasses	4 heat resistant glasses
Inner side	Full glass
hinges	Heavy duty Steady Tilt
Handle	Satin finish Stainless steel handle

Technical Specifications

Electric supply	120/240VAC - 60Hz // 120/208VAC - 60Hz
Max Amp usage, power rating (240V,60Hz)	16,9 A - 3,84 kW
Max Amp usage, power rating (208V,60Hz)	17,5 A - 3,54 kW
cable + conduit	yes
certification	USA & CA (ETL)
Warranty	24 months
Installation & user manual:	EN, FR, SP

Delivered accessories

Chromed racks	2
telescopic chromed rack	1
Enamelled grill set	1
Meat Probe	1

