

Foster Ranges

Foster Milano Induction Range - 48" x 27" - 7170 900

OVEN SPECIFICATONS

Model	Milano 30" single BM
Oven Type	Multifunction Pyrolytic Oven
Door finishing	Black Mirror glass
cooking Functions	13
Control Type	Electronic
Temperature control	Electronic
Commands	2 knobs / 6 touch keys
Language	English
Special features	
Cleaning function	Pyrolytic self clean
Probe T control	yes
Preset/last used temperature memory	yes
Preheat bar (25%, 50%, 75%, 100%)	yes
Automatic fast preheat	yes
Sabbath mode	Yes
Safety	Keyboard lock, Child door lock
Temperature unit	°C/°F
Clock format	12/24 Hours
Cooking Functions	Pyrolytic Sel Clean with automatic door lock; Dual convection Bake; convection Broil; Convection Roast; Lower Convection (Pizza function); Bake; Broil; Delicate cooking; Defrost; Proof warm; Keep warm (warm plus); Light; Fast preheating.
Cavity	
Usable capacity	4,1CuFt
cavity finish	Dark gray pyrolytic enamel
Rack positions	6
Lighting	Triple asymmetrical halogen (20W) lighting
Broil upper heating element	3500 W (240 V)
Upper aux element	1032 W (240 V)
Concealed bake lower heating element	3000 W (240 V)
Convection element	2 x 1300 W (240 V)
Door	
door Glasses	4 heat resistant glasses
Inner side	Full glass
hinges	Heavy duty Steady Tilt
Handle	Satin finish Stainless steel handle
Technical Specifications	
Electric supply	120/240VAC - 60Hz // 120/208VAC - 60Hz
Max Amp usage, power rating (240V,60Hz)	16,9 A - 3,84 kW



Max Amp usage, power rating (208V,60Hz)	17,5 A - 3,54 kW
cable + conduit	yes
certification	USA & CA (ETL)
Warranty	24 months
Installation & user manual:	EN, FR, SP
Delivered accessories	
Chromed racks	2
telescopic chromed rack	1
Enamelled grill set	1
Meat Probe	1

RANGETOP SPECIFICATONS

Model	Milano Induction Rangetop
Dimensions	47 7/8" x 27"
Maintop	AISI 304 Stainless steel
Finish	Satin Finish
Induction cooker hob:	
Settings	9 plus Powerboost
Commands	5 slider commands
Special functions:	Bridge, T-Chef, Pause and Recall, Independent timer, Security lock, Residual heat light, Overflow detection
Power	
4 zones size 7x8"	1.900-2.200 W (3.400-3.900 Booster)
1 zone size 7x10"	2.400-2.800 W (5.000-5.800 Booster)
Electrical supply	208-240V - 50/60 Hz

Foster Ranges

Foster Milano Induction Range - 48" x 27" - **7170 900**

DRAWING

