23 538 ESSENCE

SINGLE HOLE SINGLE-HANDLE DECK MOUNT VESSEL SINK FAUCET 1.2 GPM

STANDARD SPECIFICATION:

- GROHE SilkMove[®]
- GROHE StarLight[®]
- GROHE QuickFix[®] Plus
- GROHE AquaGuide adjustable aerator 20°-40°
- 14 5/16" Faucet height
- 7 1/16" Swivel spout reach
- 12 ¹¹/₁₆" Aerator height
- Capability to have a 90° or 360° swivel radius
- High temperature limit stop
- Solid brass body
- 23 1/2" Nylon braided flex hoses
- CALGreen/CEC compliant
- 1.2gpm (WaterSense)
- Vessel sink pop-up drain (65 818) sold separately
- Grid drain (28 951) sold separately



PRODUCT FEATURES:

- GROHE StarLight®
- GROHE SilkMove®

GROHE QuickFix®

CERTIFICATIONS:



- ADA
- WaterSense
- CEC Certified
- Low Lead Certified
- CALGreen Compliant
- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- NSF 61
- CSA B125.1
- ASME A112.18.1
- · Complies with lead plumbing laws

AVAILABLE FINISHES:



NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 06-28-2022

US Tel: 1.630.582.7711 Fax: 1.630.582.7722 For the most current Specification Sheet, go to www.grohe.us. Canada Tel: 1.888.644.7643 Fax: 1.905.366.2071 For the most current Specification Sheet, go to www.grohe.ca.



Pure Freude an Wasser



23 538 ESSENCE

SINGLE HOLE SINGLE-HANDLE DECK MOUNT VESSEL SINK FAUCET 1.2 GPM

Pure Freude an Wasser



TECHNICAL DATA:

Product Height	14-5/16 in
Product Length	8 in
Product Width	3-15/16 in
Fitting Spout Height	12-11/16 in
Fitting Spout Reach	7-1/16 in
Fitting Handle Height	7-1/2 in
GPM (Min)-GPM (Max)	1.2 gal (US)/min
Fitting No of Holes Required	1

