

# SPEAKMAN® SE-7001

## Heat Traced Combination Shower with Eye/Face Wash System

### FEATURES:

- Wrapped with heat trace cable, insulation, easy access shell to protect to -50°F
- Activated by Powder coated high visibility yellow, aluminum triangular pull rod
- 8 in. Diameter yellow plastic showerhead
- Freeze Valve activates automatically below 40°F
- 1 in. NPTF chrome plated brass stay-open ball valve
- 1 in. IPS galvanized steel pipe
- 1 in. NPT male, top supply inlet
- 20 gpm @ 30 psi
- Universal emergency sign included

### EYE/FACE WASH FEATURES:

- (2) yellow plastic spray outlets with automatic flow control and flip-top dust caps
- ½ in. NPT, 3-way chrome plated brass ball valve
- 4.5 gpm @ 30 psi
- Stainless steel push handle activation

### ELECTRIC:

- Self-regulating heating cable with braided metal shield
- Preset, hermetically sealed single pole contact switch. Temperature range 60° to 70° F thermostat
- Closed cell rubber foam insulation
- NEMA 4X water tight and dust tight, suitable for indoor or outdoor locations junction box
- 120 vac, 60 cycle, single phase
- Electrical Classification Class 1 Division 2 GRP: B, C, D
- Ground Fault Protection: Installation will require minimum 30 mA GFFPD

### COMPLIANCE:

- Certified to ANSI/ISEA Z358.1

### OPTIONS:

Add suffix to model #

Integral:

- Drench hose option  -DH
- Immersion well thermometer  -IT
- Scald protection valve  -SPV
- 1 in. union  -UN1

Field Installed Accessories:

- Area light for Class 1 Division 2 areas - clear globe  -VPL-C1D2
- Pilot light for Class 1 Division 2 areas  -PL-C1D2
- Area light for Class 1 Division 2 areas - clear globe  -VPL-C1D2

### WARRANTY:

- 3 year limited



Architect/Engineer Approval Space:

SPEAKMAN  
400 ANCHOR MILL ROAD  
NEW CASTLE, DE 19720

P: 800-537-2107  
F: 800-977-2747  
W: WWW.SPEAKMAN.COM  
R: MARCH 2017

**DIMENSIONS:** NOTE: 1. All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice.

